

**High Output LED Strip-lights**



**Features**

- Direct replacement in existing fittings
- ‘G13 (EN 60061-2) Connections’
- No ‘inverters or ballast’ required
- High light output
- Low power consumption
- Long life
- Choice of sizes & voltages
- Robust assembly
- RoHS compliant
- RIA 12-13 Report No. RTCL-TD-2010-IG3
- Bridging circuit (No polarity issues)

Catalogue No	LED600/24	LED900/24	LED1200/24	LED1500/24	LED1800/24	LED600/90-250	LED1200/90-250	LED1500/90-250	LED1800/90-250
Nom. Tube Length (mm)	600	900	1200	1500	1800	600	1200	1500	1800
LED Size (Ø)	5								
Total No. of LED's	180	222	288	324	414	180	288	324	414
Colour temp.	Neutral White 400-5500K								
Beam angle (deg)	120								
Light intensity (Lumens)	900	1850	2560	3870	4480	900	2560	3870	4480
Housing material	Aluminium body & acrylic diffuser								
Life (hrs)	> 60,000								
Power Consumption (W)	9	13	15	18	22	9	15	18	22
Voltage (V)	24V AC/DC					110V AC/DC			
Operating temp (°C)	-25°C to +85°C								

**“The brightest idea in LED lighting”**